

# Inserti filettati antivibranti PRENSERT

PRENSERT anti-chatter rivet nuts

NPTC

34800

## Neoprene




Neoprene




## Inserto filettato in ottone

Brass rivet nut

## Testa tonda

Dome head



d		T	k	SS	L	Tipo	Codice			
mm	mm	mm	max	mm	mm	Model	Item code	pz	pz	
M3	8.0 ÷ 8.3	11.0	1.4	0.4 ÷ 4.0	12.6	NPTC0304008	2394400	250S	5000	
M4	8.0 ÷ 8.3	11.0	1.4	0.4 ÷ 4.0	12.6	NPTC0404008	2394500	250S	5000	
M5	9.7 ÷ 9.9	12.7	0.9	0.4 ÷ 4.9	14.1	NPTC0504910	2394600	250S	5000	
		14.0	0.9	4.0 ÷ 11.6	21.5	NPTC0511610	2394700	250N	2000	
M6	12.8 ÷ 13.0	9.7 ÷ 9.9	1.3	7.9 ÷ 16.0	26.1	NPTC0516010	2394800	250P	1500	
		14.0	1.3	20.5 ÷ 30.0	39.8	NPTC0530010	2394900	250P	1000	
		16.0	1.3	0.4 ÷ 2.8	16.0	NPTC0602813	2395000	250N	2000	
M8	16.0 ÷ 16.2	12.8 ÷ 13.0	4.75	0.8 ÷ 4.7	21.1	NPTC0604713	2395200	200P	1000	
		12.8 ÷ 13.0	16.3	2.0	6.4 ÷ 11.5	26.7	NPTC0611513	2395300	200P	1000
		13.1 ÷ 13.3	16.0	1.3	11.5 ÷ 23.0	35.0	NPTC0623013	2395400	100N	800
M8	16.0 ÷ 16.2	22.1	3.2	0.4 ÷ 4.0	18.3	NPTC0804016	2395500	100N	1000	
		22.1	5.72	3.9 ÷ 9.5	27.9	NPTC0809516	2395600	100P	800	
M10	20.1 ÷ 20.3	18.1 ÷ 18.3	1.6	15.0 ÷ 39.0	50.0	NPTC0839018	2395700	50N	500	
		22.5	1.3	19.0 ÷ 40.0	55.0	NPTC1040020	2395800	50P	200	
M12	24.1 ÷ 24.3	27.0	1.3	38.0 ÷ 64.0	80.0	NPTC1264024	2395900	25P	100	






Applicazione

Application

Consigliato per eliminare problematiche di rumori che derivano dalle vibrazioni.

Recommended to avoid problems of noise or on parts subject to vibration.



d			Durezza	Kgm	Nm
mm	mm	mm	Hardness		
M3	8.0 ÷ 8.3	8.0 ÷ 8.3	60	0.25-0.50	2.5-5.0
M4	8.0 ÷ 8.3	8.0 ÷ 8.3	70	0.25-0.40	2.5-4.0
M5	9.7 ÷ 9.9	9.7 ÷ 9.9	60	0.35-0.50	3.5-5.0
		9.7 ÷ 9.9	60	0.30-0.89	3.0-8.9
M6	12.8 ÷ 13.0	9.7 ÷ 9.9	60	0.30-0.69	3.0-6.9
		9.7 ÷ 9.9	60	0.59-0.99	5.9-9.9
		12.8 ÷ 13.0	60	0.59-0.99	5.9-9.9
M8	16.0 ÷ 16.2	12.8 ÷ 13.0	60	0.79-0.99	7.9-9.9
		12.8 ÷ 13.0	70	0.79-0.99	7.9-9.9
		13.1 ÷ 13.3	70	0.79-0.99	7.9-9.9
M8	16.0 ÷ 16.2	16.0 ÷ 16.2	60	0.99-1.48	9.9-14.8
		16.0 ÷ 16.2	60	0.99-1.57	9.9-15.7
M10	20.1 ÷ 20.3	18.1 ÷ 18.3	60	0.99-1.57	9.9-15.7
		20.1 ÷ 20.3	60	4.40-5.40	44.0-54.0
M12	24.1 ÷ 24.3	24.1 ÷ 24.3	60	5.90-6.90	59.0-69.0