

Inserti filettati per materiali soft TUBRIV

TUBRIV rivet nuts for soft materials

TBF




34701

■ Acciaio

Steel

Fusto cilindrico aperto

Open cylindrical shank



d		T	k	SS	L	L ₂	Tipo	Codice		
mm	mm	mm	max	mm	mm	mm	Model	Item code	pz	pz
M4	6.15	11.0	0.96	0.5 ÷ 3.80	16.6	8.6	TBF0403806	52155ZB	250S	8000
M5	7.50	12.5	0.96	0.5 ÷ 4.45	21.0	9.9	TBF0504407	37430ZB	250N	4000
M6	9.00	15.5	1.50	0.5 ÷ 7.10	25.0	12.8	TBF0607109	17500ZB	200N	2000
M8	11.50	19.0	1.57	0.5 ÷ 7.10	28.0	14.5	TBF0807111	17498ZB	100N	1000
M10	13.10	22.0	2.24	0.5 ÷ 7.10	31.0	15.8	TBF1007113	52156ZB	100N	1000

Consigliato per essere applicato su compensato, plastica, vetroresina, ecc.

Recommended to be applied on plywood, plastic, fiberglass, etc.




Applicazione
Application



Attrezzo per la posa RIV916
Relating tool RIV916
Cod. 4154500



Attrezzo per la posa RIV903C
Relating tool RIV903C
Cod. 3675800



d		Kg	N	Kgm	Nm
mm	mm				
M4	6.15	700	7000	0.5	5.0
M5	7.50	1000	10000	0.8	8.0
M6	9.00	1920	19200	1.2	12.0
M8	11.50	2540	25400	2.1	21.0
M10	13.10	3000	30000	3.0	30.0